

External 192V Tower Battery Pack for select Tripp Lite UPS Systems (BP192V1407C-1PH)

MODEL NUMBER: **BP192V1407C-1PH**



Highlights

- Extends runtime of compatible Tripp Lite UPS Systems using 192VDC configuration
- Includes built-in 7A charger
- Includes UPS connection cabling
- 10 year design life
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Description

Tripp Lite's BP192V1407C-1PH External Battery Pack with built-in 7A charger offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Includes heavy gauge cabling to connect to host UPS. Multiple BP192V1407C-1PH batteries can be daisy-chained for longer runtime configurations with appropriate contractor-supplied battery pack interconnection cabling (see manual). Internal battery charger is powered via hardwire connection to 120V 30A electrical service.
 COMPATIBLE UPS SYSTEMS: SU5000RT4U, SU6000RT4U, SU8000RT4U and other Tripp Lite UPS systems specifying the use of this battery pack.

Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- 10 year design life
- Multiple battery packs can be daisy-chained through each other to the UPS for even longer extended run operation
- Cabling to connect one BP192V1407C-1PH is included - cabling for additional battery packs is contractor supplied
- Includes built-in 7A charger powered via hardwire 120VAC 30A input connection

Specifications

| OVERVIEW | |
|----------|--------------|
| UPC Code | 037332146717 |
| BATTERY | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|--|
| Expandable Battery Runtime | Multiple battery packs can be daisy-chained to the UPS for extended runtime. Configuration specific cabling for multi-battery pack configurations is contractor provided. |
| DC System Voltage (VDC) | 192 |
| UPS Connection | Included cabling enables connection between unique UPS connector and hardwire DC terminals in battery pack. Cabling to connect multiple external battery packs is contractor provided. |
| Expandable Runtime | Yes |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 0.000 x 0.000 x 0.000 |
| Shipping Dimensions (hwd / cm) | 0.00 x 0.00 x 0.00 |
| Shipping Weight (lbs.) | 2075.0000 |
| Shipping Weight (kg) | 941.20 |
| Unit Dimensions (hwd / in.) | 60 x 32.4 x 28.8 |
| Unit Dimensions (hwd / cm) | 152.4 x 82.3 x 73.2 |
| Unit Weight (lbs.) | 2070 |
| Unit Weight (kg) | 938.94 |
| Material of Construction | Steel |
| External Battery Pack Form Factor | Tower |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>